

RNTD Rotary Slip Preset Torque Screwdriver

Direction



RNTD120CN with Resin Grip

Assembly Preset Rotary Slip ISO6789:2003

- Preset version of RTD
- No external scale, torque set by a torque driver tester

Accuracy ±3%

Model	Torque Range			Overall Length [mm]	Weight [g]
	[cN·m] Min.-Max.	[kgf·cm] Min.-Max.	[lbf·in] Min.-Max.		
RNTD15CN	5-15	0.5-1.5	0.5-1.3	95	71
RNTD30CN	10-30	1-3	0.9-2.5		
RNTD60CN	20-60	2-6	2-5		
RNTD120CN	40-120	4-12	4-10	110	110
RNTD260CN	100-260	10-26	9-23		180
RNTD500CN	200-500	20-50	20-40	120	270

Note
 1. A torque driver tester is necessary for torque setting.
 Specify required set torque when you order. Ex. RNTD120CN x 100cN·m
 2. Torque adjusting bar is sold separately. Refer to page 49.
 3. Bits are sold separately. Refer to page 10.

Standard Accessories
 1. Resin grip for RNTD120CN and RNTD260CN
 2. Auxiliary tightening bar for RNTD500CN

NTD Preset Torque Screwdriver

Direction



NTD120CN with Resin Grip

Assembly Preset ISO6789:2003

- Preset version of LTD
- No external scale, torque set by a torque driver tester

Accuracy ±3%

Model	Torque Range			Overall Length [mm]	Weight [g]
	[cN·m] Min.-Max.	[kgf·cm] Min.-Max.	[lbf·in] Min.-Max.		
NTD15CN	5-15	0.5-1.5	0.5-1.3	95	70
NTD30CN	10-30	1-3	1-2.5		
NTD60CN	20-60	2-6	2-5		
NTD120CN	40-120	4-12	4-10	110	110
NTD260CN	100-260	10-26	10-22		180
NTD500CN	200-500	20-50	20-40	120	270
NTD1000CN	400-1000	40-100	40-88	155	550

Note
 1. A torque driver tester is necessary for torque setting.
 Specify required set torque when you order. Ex. NTD120CN x 100cN·m
 2. Torque adjusting bar is sold separately.

Standard Accessories
 1. Resin grip for NTD120CN and NTD260CN
 2. Auxiliary tightening bar for NTD500CN and NTD1000CN

RTDZ Insulated Rotary Slip Adjustable Torque Screwdriver

Direction



RTDZ260CN

Assembly Adjustable Rotary Slip Resin Body Insulated ISO6789:2003

- Insulated design suited for use in electric shock hazard conditions
- Ideal for electric car assembly, connection of battery terminal wiring work etc

Accuracy ±3%

S.I. Model	Torque Range [cN·m]		Metric Model	Torque Range [kgf·cm]		Torque Range [lbf·in]		Overall Length [mm]	Weight [g]
	Min.-Max.	Grad.		Min.-Max.	Grad.	Min.-Max.	Grad.		
RTDZ260CN	60-260	2	26RTDZ	6-26	0.2	-	-	150	220
RTDZ500CN	100-500	5	50RTDZ	10-50	0.5	-	-	183	380

Note
 1. Torque adjusting bar is sold separately.
 2. Bits are sold separately. Refer to page 10.
 3. Bits are not insulation coating.

RNTDZ Insulated Rotary Slip Preset Torque Screwdriver

Direction



RNTDZ500CN

Assembly Preset Rotary Slip Resin Body Insulated ISO6789:2003

- Insulated design suited for use in electric shock hazard conditions
- Ideal for electric car assembly, connection of battery terminal wiring work etc

Accuracy ±3%

S.I. Model	Torque Range [cN·m]		Metric Model	Torque Range [kgf·cm]		Torque Range [lbf·in]		Overall Length [mm]	Weight [g]
	Min.-Max.	Grad.		Min.-Max.	Grad.	Min.-Max.	Grad.		
RNTDZ260CN	100-260	-	-	10-26	-	10-22	-	123	240
RNTDZ500CN	200-500	-	-	20-50	-	20-40	-	138	340

Note
 1. A torque driver tester is necessary for torque setting.
 Specify required torque when you order. Ex. RNTDZ260CN x 200cN·m
 2. Torque adjusting bar is sold separately.
 3. Bits are sold separately. Refer to page 10.
 4. Bits are not insulation coating.

Torque Screwdriver

